

LED Ceiling Light

A5

·Universal Application



INDOOR

A5
LED Ceiling Light



1.Features

- Environmentally friendly alternative to traditional lighting.
- Resistant to ambient temperatures up to 60°C.
- Lifetime over 50.000 hours.
- 5 Years warranty
- High Power LEDs.

5 Years
Warranty



2.Parameter



Item Code	Power	Size	IP LEVEL	Material
LU-230C-40	12	Ø230mm	IP40	PC
LU-260C-40	15	Ø260mm	IP40	PC
LU-300C-40	18	Ø300mm	IP40	PC
LU-350C-40	24	Ø350mm	IP40	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-230C-40B	18	Ø230mm	IP40	PC
LU-300C-40B	24	Ø300mm	IP40	PC
LU-350C-40B	36	Ø350mm	IP40	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-230C-40C	12	Ø230mm	IP40	PC
LU-230C-40C	18	Ø230mm	IP40	PC
LU-300C-40C	24	Ø300mm	IP40	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-320C-40D	18	Ø320mm	IP40	PC

Other Parameter

Input Voltage: AC220-240V
CCT:3000K/4000K/6000K
LED Chips: SMD2835
CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-320C-40E	18	Ø320mm	IP40	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-300C-40F	24	300*300mm	IP40	PC
LU-400C-40F	36	400*400mm	IP40	PC
LU-500C-40F	48	500*500mm	IP40	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-280C-44B	12	Ø280mm	IP44	PC
LU-280C-44B	15	Ø280mm	IP44	PC
LU-280C-44B	18	Ø280mm	IP44	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-210C-65A	10	Ø210mm	IP65	PC
LU-280C-65A	15	Ø280mm	IP65	PC
LU-360C-65A	22	Ø360mm	IP65	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra



Item Code	Power	Size	IP LEVEL	Material
LU-280C-65B	12	Ø280mm	IP65	PC
LU-335C-65B	18	Ø335mm	IP65	PC
LU-335C-65B	24	Ø335mm	IP65	PC

Other Parameter

Input Voltage: AC220-240V

CCT:3000K/4000K/6000K

LED Chips: SMD2835

CRI :>80Ra